



Vega Smart Traffic Light

Automatic Number Plate Reader

▼ *The new concept to safeguard the intersections*

Smart Traffic Light allows the red light status identification through image analysis.

Red light violation detected by image

analysis (without external sensors), no external device required and reduced installation and maintenance costs.

The system is able to manage different kinds of traffic installations (one or two lanes, one traffic light each lane or every two lanes).



▼ Ability to recognise every plate passing under the camera and not only violators. This is very useful for security or statistical purposes

▼ All transit plates are recorded and available for:

- Red light enforcement
- Tax and insurance control
- Vehicle tracking
- Traffic monitoring

▼ *Application*

- Enforcement
- Traffic monitoring
- Security

Traffic Light Enforcement

SMART TRAFFIC LIGHT	
Software features and Performance	
Lane Detected	2
Max Vehicle Speed [km/h]	250
Working Distance [m]	up to 25
Detection	99%
Reading	>95%
OCR	ANPR engine on board
2nd Lever OCR	optional
Grabbing	75 fps
Classification	optional
Vehicle Color	optional
Vehicle Brand	optional
Vehicle Model	optional
AES256	Yes
SHA2	Yes
Compression	JPG
Streaming	Video streaming via standard RTSP protocol
Configuration	
Web Server	Installation and configuration by Web Server on board
TCP/IP Server	Configuration and monitoring through TCP/IP protocol. (SDK provided)
Date and Hour	Synchronization via NTP protocol, IEEE1588, GPS
Software Update	Upgrading via Web Interface and SDK
Data Transmission	
FTP	FTP Client to FTP Server mode for remote data transmission; Multiple IP servers addressable
TCP/IP	Tattile TCP/IP open protocol; (SDK provided)
Standard protocols	XML; SNMP; NTCIP; DATEX2; UTMIC; ONVIF; MODBUS
Serial Port	Insulated RS485

SMART TRAFFIC LIGHT	
Op. Mode	
Free Run	Continuous processing with automatic vehicle detection, even without plate
Triggered	Image capture and processing triggered by Ethernet command or digital signal
System	
ANPR camera	5 MPX BW 5 MPx Color (color version)
Context camera	2.3 Megapixel color CMOS sensor
Illuminator	12 high power LEDs, InfraRed @ 850 nm
Lenses	C-Mount. Many focal lengths available
Operating System	Linux Operating System
Digital i/o	6 Optoisolated input - 4 Relay Output - 1 Strobe output
Connectors	Waterproof circular connector
IP Protection	Waterproof IP68
Ethernet	GigaBit Ethernet 10/100/1000
Storage	uSD up to 128 GB HD/SSD up to 1 TB
GPS	Optional
LTE	Optional
WiFi (Easinstall)	Yes
Technical Datas	
Operating & Storage Temperature	From -40° to +55° C
Operating & Storage Humidity	From 10% to 90% non condensing
Dimensions	290 x 127 x 235 mm (WxHxL)
Weight [kg]	5.5
Power supply voltage	24 Vdc
Power consumption	50 W (max)

